

QMFZ2.E132532

Plastics - Component

LORENZ KUNSTSTOFFTECHNIK GMBH
 HANSASTRASSE 75
 49134 WALLENHORST, GERMANY

E132532

									H	D	
		Min.		H	H	RTI			V	4	C
		Thk	Flame	W	A	Elec	Mech		T	9	T
Material Dsg	Color	mm	Class	I	I		Imp	Str	R	5	I
Bulk Molding Compound "Polyester" (BMC), glass reinforced, furnished as bulk.											
KFX	ALL	1.5	V-0	-	-	105	130	130	0		0
		2.0	V-0	0	0	105	130	130			
		3.0	V-0	0	0	105	130	130			
MK2753	NC	1.5	HB	3	2	130	130	130	0	5	
		3.0	HB	2	2	130	130	130			
		6.0	HB	0	2	130	130	130			
Bulk Molding Compound "Polyester" (BMC), furnished as granular material, bulk, powder.											
803/1430 UF3											
	GY	1.5	HB	1	-	105	130	130	0	4	
		3.0	V-0	0	-	105	130	130			
		6.0	V-0	0	-	105	130	130			
UP R1420 LSF											
	NC, GY	1.5	HB	0	0	130	130	130			0
		3.0	V-0	0	0	130	130	130			
UP1420UFL, 2621-V9											
	ALL	1.5	HB	1	-	130	130	130	0	4	
		3.0	V-0	0	-	130	130	130			
UP1430LSF	ALL	1.5	HB	1	0	130	130	130	0	4	0
		3.0	V-0	0	0	130	130	130			
Sheet Molding Compound "Polyester" (SMC), furnished as sheets.											

UP-RM 422 S-LSF											
	ALL	3.0	V-0	-	-	105	130	130			
UP-RM 422 SF/R8											
	BK	3.0	V-0	-	-	105	130	130			
UP-RM 427 C-F/R8 (f1)											
	GY	1.5	HB	-	-	105	130	130			
UP-RM 427 UFE (f2)											
	GY	3.0	V-0	-	-	105	130	130			
UP-RM 430 LSF(f1)											
	WT	3.0	V-0	-	-	105	130	130			
Unsaturated Polyester (UP), glass reinforced, "LOMIX", furnished as bulk (BMC) or sheet (SMC) molding.											
BMC 0040/P(xxx)											
	ALL	3.0	V-0	-	-	105	130	130			
Unsaturated Polyester (UP), "LOMIX", furnished as bulk (BMC) or sheet (SMC) molding compound.											
BMC 0104/P(xxx)											
	ALL	2.0	V-0	0	1	105	130	130			0
		3.0	V-0	0	1	105	130	130			

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

(f2) - Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL Inc.(xxx) - Denotes a 3 digit number representing color code.

Marking: Company name and material designation on container, wrapper or finished part.